

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

# Technical Datasheet ✓ RoHS<sub>2</sub> 2002/95/EC 2011/65/UE

## tasker® C113 - 1x0,25 mm<sup>2</sup> - Spiral Shielded Cable



A	B	C	D
---	---	---	---

**CATEGORY**    Spiral Shielded Cables (See Audio Catalogue)  
**APPLICATIONS**    Sound Reproduction and Electronics

- A:**        Black Soft **PVC** Sheath. Outer Diam. Ø 3,00 (±0,20) mm.
- B:**        Shielded with O.F.C. red copper spiral covering 100%.
- C:**        Core Insulation with Red PVC – Diam. Ø 1,50 (±0,10) mm.
- D:**        O.F.C. red copper formation 8x0,20 mm.  
               Nom. Cross section 1x0,25 mm<sup>2</sup>.

**MARKING**        **tasker®** C 113 1x0,25 mm<sup>2</sup> O.F.C. Shielded Cable  
**CUSTOM**        This product may be custom produced also in **LSZH, PE, PUR,**  
**PRODUCTION**    with or without Metallic Armor.

### Cable Properties

<b>Conductor Resistance</b>	75 Ω/Km
<b>Capacity Core/Shield</b>	460 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			