

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C139 2x0,08 mm² (75Ω)

Special Video Cable



A	B	C	D	E
---	---	---	---	---

CATEGORY Video Cables (See Video Catalogue)
APPLICATIONS S-VHS and Video assembly

- A:** Night Blue Soft **PVC** Sheath.
Outer Diam. Ø 7,50 (±0,20) mm.
- B:** Inner sheath in PVC colored one white and one red.
Outer Diam. Ø 2,80 (±0,20) mm.
- C:** Spiral shielding in of O.F.C. tinned copper, covering 100%.
- D:** Insulation with White PEE. Diam. Ø 1,50 (±0,20) mm.
- E:** Stranded O.F.C. red copper formation 10x0,10 mm.
Nom. Cross section 2x0,08 mm² (75Ω)

MARKING tasker® C139 2x75Ω O.F.C. S-VHS Video Cable
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

General Properties:

Conductor Resistance	203 Ω/Km
Impedence	75 Ω
Velocity of Propagation	66 %
Capacity Core/Shield	67 pF/m
Max rated Voltage	49 V
Operative Temperature	-15/+70°C

Attenuation dB/100 mt.

50 MHz	19,50
100 MHz	28,50
200 MHz	41,70
400 MHz	60,20
800 MHz	87,30
1000 MHz	103,00

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			