

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C142 2x0,08 + 2x0,25 mm²

Special Video Flat Divisible Cable



CATEGORY Video + Audio Cables (See Video Catalogue)
APPLICATIONS Video and Audio Stereo assembly

A: Night Blue Soft PVC Sheath.
 Outer Dimension: 5,00x14,50 (±0,20) mm.

Audio Section:

- B:** Spiral shielding in of O.F.C. red copper, covering 100%.
- C:** Insulations in compact PE, colored one red and one white.
 Diam. Ø 2,30 (±0,20) mm.
- D:** Stranded O.F.C. red copper formation 8x0,20 mm..
 Nom. Cross section 2x0,25 mm².

S-VHS Section:

- E:** Inner sheath in PVC, colored one red and one white.
 Outer diam. Ø 2,00 (±0,20) mm.
- F:** Braid shielding in of O.F.C. tinned copper, covering 100%.
- G:** Insulation in PVC, colored one white and one yellow.
 Diam. Ø 1,00 (±0,20) mm.
- H:** Stranded O.F.C. tinned copper formation 12x0,10 mm.
 Nom. Cross section 2x0,08 mm²

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

MARKING

tasker® C 142 2x0,08 + 2x0,25 mm² Professional High Definition S-VHS Video and Audio cable Made in Italy

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Audio Section Properties

Conductor Resistance	75,85 Ω/Km
Capacity Core/Core	36 pF/m
Capacity Core/Shield	96 pF/m

Video properties

Conductor Resistance	203 Ω/Km
Impedence	75 Ω
Capacity Core/Core	65 pF/m
Capacity Core/Shield	230 pF/m

General Properties:

Max rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			